

### **Boiler Nameplate Data**

2 each

Cleaver-Brooks Four-Pass Skid Mounted Dual Fuel Boilers

CB-LE

CB Packaged Boiler

Model CB-I-200-300 LE

Maximum Pressure: 15 PSI

Input: 12,293,000 Btu/Hr of Natural Gas

or 88.8 Gph of Oil

Main electrical power requirements: 208 volts, 3 phase, 44.5 amps, 60 cycle

Control circuitry power requirements: 120 volts, 1 phase, 7.0 amps, 60 cycle

Maximum circuit ampacity: 52.5 amps

Maximum rating of circuit protection: 170 amps

Blower motor: 10 hp

Air compressor: 3 hp

Underwriters Laboratories Inc. Label

No.: AN82007

For 4D Gas and 4D Oil, Oil not heavier than No. 2

Date of manufacture: 15/07/96

Serial Numbers: L-95543 and L-95544 respectively

### **Options Included:**

Cleaver Brooks Burner Controls, dynamic ampli-check infrared flame amplifier, natural gas train with valves, oil pump unit, low Nox emissions package (60 ppm Nox), 2" fiberglass insulation, integral forced draft burner, two motorized gas SSOV's, one with proof of closure, magnetic motor starters, indicating panel lights, pressure switches, solenoid valves, and more! See photographs for further details.

Note: These units were designed and constructed to the following: ASME Code, IRI & New York State Education Compliance.